



TENAGA KIMIA SENDIRIAN BERHAD (26191 A)

Administration & Sales Office

Address: No. 8, Jalan SS 22/21, Damansara Jaya, 47400 Petaling Jaya, Selangor
Tel: + 60 – 3 – 7729 7464
Fax: + 60 – 3 – 7729 8383
E-mail: sales@tenagakimia.com

Factory

Address: Lot 5065, 48100 Batu Arang, Selangor, Malaysia
Tel: + 60 – 3 – 6035 2801
Fax: + 60 – 3 – 6035 2802
E-mail: plant@tenagakimia.com

Website: <http://www.tenagakimia.com>

TECHNICAL DATA SHEET

PRODUCT: DETONATING CORD 10G/M
BRAND: DETONATING CORD
SERIES: DETONATING CORD

Product Specification

- (A) Appearance: Colour coded on outer sleeve of plastic, the thickness of plastic is even with no air bubbles, apertures, cracks or serious damage.
- (B) Loading Explosive: PETN
- (C) Charge Weight: 9.6 – 10.2g
- (D) Velocity of Detonation: $\geq 6000\text{m/s}$
- (E) Outer Diameter: $\leq 5.4\text{mm}$
- (F) Tensile Strength: $\geq 500\text{N}$
- (G) Water Resistance: Kept in 5m-deep water (10-25°C) or a water pressure chamber of 50kpa for 5 hours, the detonating feature should remain reliable.
- (H) Temperature Tolerance: Kept at $50^{\circ}\text{C} \pm 2^{\circ}\text{C}$ for 6 hours or at $-40^{\circ}\text{C} \pm 2^{\circ}\text{C}$ for 2 hours, the detonating features should remain reliable.

Packing Method	Packing: in cartons, 800m/carton Net weight: 21kg
Usage	For initiation of boosters or high-sensitive explosive
Cautions of Transport and storage	1: Handle with care, violent impact is strictly prohibited. 2: Keep away from detonators while transport and storage. 3: Should be evenly packed inside the train wagon or containers when loading, stack height should not more than 7 layer or 1.8 meters.
Fire fighting Method	Handle with water: do not use sand or foam fire extinguisher

